


## Ivocryl Duplex Galvanized Steel Coating System



### Description

Ivocryl Top Coat is a unique performance UV resistant single pack coating designed to be used in conjunction with Ivocryl Straw Primer to provide outstanding protection to galvanised roofs, masts and structural steel.

### Uses

- Protection of new or existing galvanised masts or roofs.
- Rejuvenation and protection of old corrugated fibre cement roofs subjected to industrial fall out.
- Rejuvenation of "Chromadek".
- High performance exterior wall coating.

### Preparation

Ensure surfaces are clean and free of contaminants. See details in Ivory Ivocryl Straw Primer data sheet.

### Technical Information

The figures that follow are typical properties achieved in laboratory tests at 20 °C and at 50% Relative Humidity.

No of components	:	Single Pack
Colours	:	
International Orange, White, Brunswick Green, Grey		
Finish	:	High Sheen
Theoretical coverage	:	8m <sup>2</sup> /ℓ
Wet Film Thickness	:	125 microns
Over coating time	:	
@ 25°C & 50% RH	:	2 hours
Recommended N° coats	:	1 or 2
Dry film thickness	:	35 - 40 microns
PH	:	8 – 10
S.G	:	± 1.25
Min Application Temp	:	5°C
Max Application Temp	:	40°C
Thinning	:	DO NOT THIN
Cleaning	:	Water & W.S.B.C

### Benefits

- Excellent UV resistance.
- Outstanding adhesion to aged alkyd, epoxy, acrylics, fibreglass, wood, concrete, plaster and fibre cement.
- Does not chalk, fade or change colour.
- Resistant to acid rain and industrial fall out.
- Environmentally friendly and VOC compliant.
- Quick re-coat time.
- Can be applied by brush, roller or spray.
- Easy wash up with water.

### Application

- Apply by brush, mohair roller or spray gun at 8-10m<sup>2</sup>/ℓ.
- For corrugated roofs allow 6m<sup>2</sup>/ℓ.
- For roofs or masts subject to aggressive chemical or corrosive environments, two topcoats are recommended.

#### Durban

176 Voortrekker Street  
Jacobs  
Durban  
Kwa Zulu Natal  
Tel: +27 31 461 3411  
Fax: +27 31 461 3475  
Email: southafrica@flowcrete.com

Flowcrete SA (Pty) Ltd is a subsidiary of Flowcrete Group plc

#### Johannesburg

47 Forge Road  
Spartan  
Gauteng  
Tel: +27 11 394 1980  
Fax: +27 11 394 3003

#### Cape Town

1A Gabriel place  
Cnr Gabriel & Main Road  
Plumstead  
Cape Town  
Tel: +27 21 797 0214  
Fax: +27 21 761 6664