

## Ivosheen

### Pure Acrylic Coating Based Paint

#### Description

*Ivory Ivosheen* is a finishing paint, formulated to give excellent durability for interior and exterior applications. Based on the highest grade pure acrylic emulsion Ivosheen has excellent ultra violet resistant properties ensuring extended life even under exacting environmental conditions.

#### Uses

Suitable for use on most surfaces provided that the correct surface preparation and primers are used. Highly recommended for use on the exterior walls of buildings, workshop walls, halls, stairwells, corridors, hospitals, bathrooms and ablution walls, fascia boards, asbestos down pipes.

#### Advantages

- Single pack
- No volatile solvents
- Excellent ultraviolet light resistance
- Excellent hiding power
- Non yellowing and good stain resistance
- Thermoplastic and will not embrittle
- Very low dirt retention and easy cleaning

#### Preparation

*Ivory* manufactures detergents, etchants, degreasers, de-rusters, sanitizers etc., for all preparation requirements. All surfaces to be clean, sound and dry. All existing paint surfaces to be thoroughly washed with detergent to remove any dirt. Stiff bristle or wire brushes used to remove flaking or peeling paint and oxidation products.

#### Priming

##### Concrete, Masonry, Plaster & Asbestos

1. Previously coated with good emulsion paints - clean with damp cloth and dry, no priming required.
2. Previously coated with solvent paints - lightly abrade with fine abrasive paper, clean with damp cloth and dry, no priming required.
3. Uncoated - clean with damp cloth, dry, apply one coat of *Ivory Ivoseal* at 6m<sup>2</sup>/ℓ.

#### Technical Information

The figures that follow are typical properties achieved in laboratory tests at 20 °C and at 50% Relative Humidity.

N° of components:	1
Drying Time:	
Touch Dry	½ hour
Service	6 hours
Full Cure	7 days
Over Coating Time:	6 hours
Coverage:	± 10 - 12m <sup>2</sup> /ℓ
Recommended N° of coats:	
Primer + 2 coats dependant on substrate	
d.f.t. @ 10m <sup>2</sup> /ℓ:	40 microns.
Colours:	See colour chart
Equipment Cleaning:	Water

#### Galvanized Iron, Aluminum

1. Previously coated and sound - lightly abrade with fine abrasive paper, clean with damp cloth and dry, no priming required.
2. Coated but peeling - remove all paint, wash well with detergent, dry and apply one coat of *Ivory Ivocryl* straw primer at 7m<sup>2</sup>/ℓ.

#### Timber (Fascia Boards, Panelling etc)

Apply one coat of *Ivory Ivoseal* acrylic at 8m<sup>2</sup>/ℓ.

#### Application

Apply by brush, mohair roller or airless spray.

#### Specification

Prepare and prime surfaces and apply two coats *Ivory Ivosheen* all strictly in accordance with the manufacturers detailed instructions.

#### Durban

176 Voortrekker Street  
Jacobs  
Durban  
Kwa Zulu Natal  
Tel: +27 31 461 3411  
Fax: +27 31 461 3475

Email: southafrica@flowcrete.com

Flowcrete SA (Pty) Ltd is a subsidiary of Flowcrete Group plc

#### Johannesburg

47 Forge Road  
Spartan  
Gauteng  
Tel: +27 11 394 1980  
Fax: +27 11 394 3003

#### Cape Town

1A Gabriel place  
Cnr Gabriel & Main Road  
Plumstead  
Cape Town  
Tel: +27 21 797 0214  
Fax: +27 21 761 6664