



## Kwikshine

### Description

Protective and decorative dressing for linoleum, vinyl, plastic rubber, sealed cork, concrete, slasto, terrazzo and asphalt flooring systems.

### Benefits

Armour plated, non-slip, flexible, scuff and stain resistant lustrous sheen.

### Preparation

Remove soils and old emulsion polish with Wax-Off diluted 1-10 with water using a coarse pad on an industrial floor machine or by scrubbing with a stiff brush. Thoroughly rinse with fresh water and allow to dry.

### Caution

Do not use solvent or ammoniated detergents for routine maintenance cleaning.

### Spread Rate

Approximately 70 m<sup>2</sup> per 5 litres.

### Application

Sparingly apply an even coat of Kwikshine with a soft applicator or mop. After 20 minutes apply a second coat.

### Maintenance

Occasionally mop the floor with a solution of 1 part Kwikshine to 10 parts water to replenish sheen. Sweep off dust and mop with a solution of Dishy diluted 1-50 with water or if a pleasant lingering perfume is desired use Opine diluted 1-50 parts water.

Flowcrete SA (Pty) Ltd  
176 Voortrekker Street  
Jacobs  
Durban  
Kwa Zulu Natal  
Tel: +27 31 461 3411  
Fax: +27 31 461 3475

Flowcrete SA (Pty) Ltd  
47 Forge Road  
Spartan  
Gauteng  
Tel: +27 11 394 1980  
Fax: +27 11 394 3003

Flowcrete SA (Pty) Ltd  
1A Gabriel place  
Cnr Gabriel & Main Road  
Plumstead  
Cape Town  
Tel: +27 21 797 0214  
Fax: +27 21 761 6664

Email: [southafrica@flowcrete.com](mailto:southafrica@flowcrete.com)  
Flowcrete SA (Pty) Ltd is a subsidiary of Flowcrete Group plc

[www.flowcrete.com](http://www.flowcrete.com)