



Flowseal EPW Clear

Water Based Epoxy Primer or Sealer

Description

A water dispersed, clear, low viscosity polyamide cured epoxy.

Uses

A primer and penetrating sealer particularly recommended when applying thin film epoxy coatings to dense concrete surfaces.

Benefits

- No odour-water based.
- Excellent adhesion.
- Damp tolerant-100% (no free standing water).
- Cement compatible and stable.
- Long pot life-1hour.

Substrate Requirements

- Old or new concrete must be clean and mechanically sound, free of dust, laitance and oil contamination.
- Grinding or sand blasting is recommended.
- All omegas, blow holes or cracks to be filled with Aquapaste and smoothed off prior to priming.

Installation Service

The installation should be carried out by a Flowcrete approved contractor with a documented quality assurance scheme. Obtain details of our approved contractors by contacting our customer service team or enquiring via our web site www.flowcrete.com.

Focus on the Floorzone

Flowcrete Group plc are world leaders in specialist industrial and commercial flooring. Systems available include: underfloor heating systems, floor screeds, surface damp proof membranes, decorative floor finishes, seamless terrazzo, car park deck waterproofing, tank lining systems... to name just a few. Our objective is to satisfy your Floorzone needs.

Technical Information

The figures that follow are typical properties achieved in laboratory tests at 20 °C and at 50% Relative Humidity.

No of components:	2
Mixing Ratio:	4:1
Pot Life:	6 hours
Drying Time:	
Touch Dry	2 Hours
Practical Cure	12 hours
Full Cure	7 days
Apply By:	Brush, Roller or Spray
Theoretical Coverage:	8m ² /ℓ
Application Temperature:	
Min	10°C
Max	30°C
Recommended no of Coats:	1
Overcoat Time:	12 hours min 48 hours max
Temperature Resistance:	
Dry	120°C
Wet	60°C
Colour:	Clear
Thinners:	Epoxy Thinners
Cleaner:	W.S.B.C
Shelf Life:	12 months

Important Note

Flowcrete's products are guaranteed against defective materials and the finished product.

Further Information

To ensure you are specifying a fit for purpose flooring for your project please consult our Technical Advisors on the number below or visit our website to register your interest in specifying one of the most durable floors on the market.

Flowcrete SA (Pty) Ltd
176 Voortrekker Street
Jacobs
Durban
Kwa Zulu Natal
Tel: +27 31 461 3411
Fax: +27 31 461 3475

Flowcrete SA (Pty) Ltd
47 Forge Road
Spartan
Gauteng
Tel: +27 11 394 1980
Fax: +27 11 394 3003

Flowcrete SA (Pty) Ltd
1A Gabriel place
Cnr Gabriel & Main Road
Plumstead
Cape Town
Tel: +27 21 797 0214
Fax: +27 21 761 6664

Email: southafrica@flowcrete.com
Flowcrete SA (Pty) Ltd is a subsidiary of Flowcrete Group plc

www.flowcrete.com