

2024 Revision

CEILING PAINT

Description and Application

CATEGORY

Ceiling Paint

DESCRIPTION

Ceiling Paint is an ultra matt acrylic product which allows both hiding power and good flow properties.

FEATURES

- Ultra-matt finish.
- Good flow with reduced drying time to allow for a consistent finish.

AREAS OF USE

- Ceilings

SURFACE PREPARATION AND APPLICATION

New Ceilings

1. Ensure the surface is clean and free of loose material
2. Apply 2 coats of Paintcors Ceiling Paint allowing 1 hour drying time between coats.

New Ceilings (Rhinolite)

1. Wipe the surface to remove excess powder.
2. Apply 1 coat of Paintcors Plaster Primer Premium or Plaster Primer Solvent base and allow 12 hours to dry.
3. Apply 2 Coats of Paintcors Ceiling paint allowing 1 hour drying time between coats.

PAINTCOR

SUPREME QUALITY *Since 1986*

Old Previously Painted Ceilings

1. Check the adhesion of the existing paint. If it is poor, remove all loose, peeling paint. Apply 1 coat of Paintcor AcrySeal diluted 1:1 with water to all areas to be painted. Allow to dry.
2. If the surface area is powdery, wash to remove all powder before applying one coat of Paintcor's AcrySeal Acrylic Sealer diluted 1:1 with water. Allow to dry.
3. Apply 1 or 2 coats of Ceiling Paint. Allow to dry between coats.
4. If the adhesion of the old paint is good, then apply 1 or 2 coats of ceiling paint.

APPLICATION EQUIPMENT

Apply by Brush, Sheepskin/Synthetic Roller or Spray

CLEANING EQUIPMENT

Clean all equipment with water after use.

STORAGE

Keep stored in cool, dry conditions and away from children.