



JAYCO M220 ACRYLIC SEALER.

DESCRIPTION:

Jayco Acrylic Sealer is a one component sealant for use on joint sealing applications where movements of 5 to 10% are expected. This sealant is easy to apply and shows good adhesion.

OUTSTANDING FEATURES

- Single component, no mixing required
- Primer-less - generally no priming is required. On verifiable concrete use Jayco Acrylic Sealer Primer
- Available in a range of colours
- Excellent resistance to ultra violet degradation
- Economical
- May be used on damp surfaces
- May be over-painted with all conventional paints

PHYSICAL PROPERTIES

Type	:	Acrylic polymer with selected fillers & additives
Specific gravity	:	Approx. 1.5
Solids content	:	75% minimum
Tack free time	:	30 minutes
Full cure time	:	48 Hours
Colour	:	White, grey and beige. Special colours available on request.

ADHESION:

Concrete and plaster	:	Excellent.
Aluminium	:	Excellent.
Ceramic Tiles	:	Excellent.



TECHNICAL DATA SHEET



Painted metal : Excellent.

Weathering Resistance : Excellent. May be used for interior and exterior applications.
Not recommended for fully immersed conditions.

Movement Tolerance : 5 to 10%.

APPLICATIONS

Suitable for sealing low movement joints such as window jointing, joints in prefabricated structures, sealing of cracks, Paving joints, Pre-fabricated panels.

INSTRUCTIONS FOR USE

1. Ensure all surfaces to be sealed are clean, firm and dust free. Slight dampness can be tolerated.
2. Cut the tip of the cart-ridge and then cut the nozzle to the required size. Gun sealant into the joint with a skeleton caulking gun.
3. Tool sealant surface to ensure proper contact and a neat finish. The tooling implement may be wetted with water to aid the tooling.
4. Allow 3 days curing before over-painting.

NOTE:

Do not use under total immersion

PACKING AND COVERAGE

Jayco Acrylic Sealer is supplied in 315 ml plastic cartridges. Other packs available, on request.

<u>JOINT SIZE</u>	<u>LINEAL METRES PER CARTRIDGE</u>
6 x 6 mm	8.5 meter
10 x 10 mm	3 metre
12 x 12 mm	2 metre
15 x 15 mm	1.2 metre

IMPORTANT NOTE:

Whilst all reasonable care is taken in compiling technical data on the company's products all recommendations or suggestions regarding the use of such products are made without guarantee since the conditions of use are beyond the control of the company. Should you have other problems or require further technical information, please contact our Technical Department. ***The information contained in this technical data sheet is to the***



TECHNICAL DATA SHEET

Bostik

jayco
sealants

best of our knowledge correct. NO GUARANTEE IS EXPRESSED OR IMPLIED. Users must satisfy themselves as to the efficacy of the product in their application.

jayco
sealants