

SPECIAL NEEDS GATE

SEMI-AUTOMATIC




- Provides controlled access and unassisted closing for any need, be it a trolley, wheelchair or baby buggy
- Exported worldwide



Tridey™ is a member of the Turnstar family



APPLICATIONS	<ul style="list-style-type: none"> • Suited for applications requiring low volume access and low levels of security • Used extensively in applications such as office receptions, universities, health clubs, museums and libraries
DESIGNED FOR	<ul style="list-style-type: none"> • Interior installations and covered exterior installations • Light operating conditions
AVAILABLE CONFIGURATIONS	<ul style="list-style-type: none"> • 90° opening and 180° opening • Framed and frameless options



Turney™ and Traffey™ are members of the Turnstar family

TURNSTAR 
RELIABLE ★ DURABLE ★ GUARANTEED

Technical Specifications

POWER	220 Volt AC (110 Volt AC on request)	
FREQUENCY	50Hz / 60Hz	
POWER CONSUMPTION	15W	
CONTROLLER VOLTAGE	12 Volt DC	
LOCKING MECHANISM	90° opening gate	180kg concealed magnetic lock
	180° opening gate	Solenoid operated locking mechanism
PIVOT	Self lubricating plastic bush with stainless steel pin	
GATE WING	<ul style="list-style-type: none"> Framed – 38mm stainless steel tube frame with glass clamps and 6mm toughened glass infill Frameless – 10mm toughened glass 	
INDICATOR LIGHTS	LED indicator lights (red cross, green arrow) mounted on top of gate post	
SYSTEMS INTEGRATION	<ul style="list-style-type: none"> Integrates with all access control and time & attendance systems Unlocking controlled through normally open dry contact 	
POWER FAILURE & FIRE ALARM	Fail-safe – the gate unlocks and can then be opened	
DESCRIPTION OF OPERATION	<ul style="list-style-type: none"> Gate is triggered either by means of a pushbutton, remote control or access control reader Gate can then either be pushed or pulled open Gate closes automatically and relocks 	

Manufacturing Options

DOOR CLOSER	<ul style="list-style-type: none"> Hold open floor spring door closer (holds gate open in the 90° position) - factory standard Non-hold open floor spring door closer
POWER OPTION	Battery backup with two 12 volt 7Ah batteries connected in series (option)
HANDING (90° GATE ONLY)	<ul style="list-style-type: none"> Left hand Right hand
FINISH OPTIONS	<ul style="list-style-type: none"> 304 grade brushed stainless steel 316 grade brushed stainless steel ▲ <p>▲ Suitable for corrosive environments (details available on request)</p>



SPECIAL NEEDS GATE RANGE

FRAMED 180°	FRAMED 90°	FRAMELESS 180°	FRAMELESS 90°
	<p>LEFT HAND SHOWN (ALSO AVAILABLE IN RIGHT HAND)</p>		<p>LEFT HAND SHOWN (ALSO AVAILABLE IN RIGHT HAND)</p>
A: 1260mm B: 820mm C: 1152mm D: 900mm			

© Turnstar Systems 2011